

DRY VANS



The thin-wall 4000D-X Composite® dry van features polyurethane foam core composite side walls that optimize strength and deliver a lower tare weight.

FEATURES

- Injected Polyurethane Foam Core Composite Side Wall
- Snag-Free® Interior Lining
- 80K Flush Steel Logistics Posts
- Optimized Cubic Load Space
- Stainless Steel Rear Door Frame
- 27" Deep Integrated Threshold Plate Assembly
- 20,000 lb Floor Rating
- Weathertight Hardwood Floor System
- 100% Soldered Electrical Wiring System
- 110 1/2" Rear Door Opening Height
- 12" Galvanized Steel Wearband
- 6-Post Front Wall
- Aerodynamic Utility Side Skirt USS-120A-4
- Bendix® TABS-6™ ABS System
- Composite Plate Rear Doors
- Corrosion Protection
- D.O.T. Rated I.C.C. Bumper with 7" Deep Horizontal Diagonal Reinforcing Gussets on Slider Rails
- Heavy-Duty Kingpin and Approach Plate Assembly
- Hendrickson® HKANT 40K Air Ride & Slider System
- Light Weight Aluminum Exterior Side Skin with Ultra Road Shield™ Plus (URS+)
- ConMet® Preset Plus® Premium Wheel End System
- Unique Tensioned Roof Design
- Support Leg Bracing



OPTIONS

- Air Disc Brakes
- Aluminum & Steel Side Wall System
- Anti-Dock Walk Devices and Dump Valves
- Approach Plate Reinforcing Angle
- Bendix® TABS-8™ Advanced with Trailer Roll Stability Program
- Clearance Light Packages
- Composite Floor Systems
- Custom Wearbands
- Double Deck Solutions
- EPA SmartWay® Certification
- Factory-Installed Decals
- Factory-Installed Lift Gates
- Heavy-Duty Aluminum Floors
- Pintle Hooks/Doubles
- Roll Up Rear Doors
- Severe Service Kingpin Section
- Side Doors Installation
- Skylights and Dome Lights
- Stainless Steel Vertical and Horizontal I.C.C. Bumper
- Stainless Steel Wingplates
- Tire Inflation Systems
- Translucent Roof Skin
- Tri-Axle Suspension Systems
- Utility Aerodynamic Tail (UAT)