



FLATBED TRAILERS

MULTI-AXLES



E X P E R I E N C E E X C E L L E N C E

SPECIFICATIONS

MODELS M-52, M-60, M-72, M-80 Various Lengths and Axle Combinations Available

Material

- 6061-T6 aluminum mill finish.

Construction

- Fully welded unitized construction.

Frame

- Manufactured from (2) T-sections that are assembled with center axis weld provides minimum stress to frame beams.
- Standard: 26" deep 52K 4' concentrated load.
- Options: 26" deep 60K 4' concentrated load.
- 29" deep 72K 4' concentrated load.
- 29" deep 80K 4' concentrated load.

Front

- Square corners.

Upper Coupler

- The 5/16" steel coupler plate is supported by heavy duty "Aluminum" extruded member reinforcement. Mylar tape and Eck applied between dissimilar metals for double protection against Galvanic corrosion.

Rear

- Full unitized construction weldment. DOT bumper, center filler plate with 2 steps Enclosed light pocket designed to protect rear lights and wiring.

Dock Bumpers

- (2) 16" on outside

Floor

- 1-1/4" extruded hollow core tubular sectioned. (2) Apitong nailers positioned along side rail.

Cross Members

- 5" tall channel with 2" capped top flange and 2" bottom flange. Standard spacing: 18" O.C. Optional spacing: 21", 16", 14" and 12".

Side Rail

- 6-3/4" tall open backed extrusion. Option: 6-3/4" heavy duty hollow core extrusion.

Lighting

- Truck-Lite 88 Series Harness will L.E.D. lights

Suspension

- Hendrickson AANT-230 tandem 122" spread with Hendrickson Axles, TP Bearings (*same large inner and outer bearings*) and HLX 5 Wheel Package

Controls

- Full suspension dump through ball valve control at landing gear.

A.B.S.

- 4S2M, WABCO

Brakes & Air System

- 16.5" x 7" extended service brake lining with 30/30 brake chambers, automatic slack adjusters. (1) 12" jumbo aluminum air tank, Sealco air valves.

Tires

- 11R x 22.5 14-PR premium radial tires.

Wheels

- 22.5 x 8.25 Alcoa

Drums & Hubs

- Centrifuse drums with DuraLite hubs.

Landing Gear

- Jost AX150 10 year warranty

FEATURES



Western Side Rail with Fixed Angle Winches and Fixed Strap Hooks




Quad Axle Steerable Rear Axle



J-Hook Tie Down
7900 lb working load limit



MAC Step-Up



Front Tapered Cross Members



Chain Sleeve Tie Down



Coil Well with Deck Pockets



Removable Access Panel

Scan Code to



Visit our Website

Follow Us!



1-800-795-8454

www.MACTrailer.com

